Options a	nd Accessories:				
AD-8920	Remote Display	GH-29	Bluetooth® (wireless) Adapter for GH and HRi Models		
AD-8922	Remote Controller		of the fixt models		
AD-1653	Density Determination Kit	GR-29	Bluetooth® (wireless) Adapter for GR Models		
AD-1682	Rechargeable Battery Pack (Ni-MH, external)	HR-29	Bluetooth® (wireless) Adapter HR- 60/120/200		
AD-1683	Static Eliminator	AD-100-2	Anti-Theft Device		
AD-1191	Compact Printer with Time & Date	CC:103E	Carrying Case (for HR-60, HR-120, HR-200 only)		
AD-8121B	Compact Printer with Time,		TIK 200 OTHY)		
	Date and Statistics	HR-03	RS-232C is standard for all HR-I, GH & GR Models		
AD-8118A	Universal Printer		GH & GR MODELS		
AD-8118B	Multi-Function Printer	HR-05	20mA Current Loop Interface; (HR-60, HR-120 & HR-200 only)		
Win-CT	Data Collection Software	HR-09	Rechargeable Battery Pack (internal, for HR-60, HR-120 & HR-200 only)		
The same of the sa			1271 74 TO 10 TO 10 TO 100 TO		



AD-1683 Static eliminator

AD-1683 static eliminator, which incorporates a high-voltage power source, is a DC power-operated small-size device which can eliminate static electricity from charged objects without the need of an external high-voltage power source. Since this static eliminator is compact and lightweight with no fan (no breeze is produced), and requires no high-voltage wiring, it is very easy to handle. Being of a DC type, it has a remarkable ability for generating ions.



AD-8922 Remote controller

AD-8922 is a remote controller that can be connected to certain A&D weighing instruments in order to display weighing data and control the weighing instrument with key operation. (Access to the internal setting of weighing instrument is not allowed.)

	AD-8922 Key Functions						
Access Device	ON: OFF	CAL	SAMPLE	PRINT	MODE	RE-ZERO	
6H, 6P, 6X, 6X-K		Calibrates using	Turns the			Name and Address of the	
GR	Turns the display	Internal mass	minimum weighing value on and off #1)	Output seighing data to en	Switches the weighing unit #1)	Heturns weighing wature to zero (tare)	
AD-4217, EK-H, GF, GF-K HR, HR-I	to be no	-					
EK-I, EW-I	144	-	-	external			
EK-G, EW-G, FC-I, FC-SI, FG, FR PS, FS-KL, HV-G, HV-WP, HW-G, HW-WP	-	-		device #2)	-	-	

#1) Excluding PCS and % mode. #2) When the weighing machine is in stream mode, and AD #522 is in key mode. #3) Excluding AD-#212